


QBiX-GLKA5005H-A1

QBiX Industrial Embedded System
Quick Start Guide



Copyright Notice

This document is copyrighted, 2019. All rights are reserved. The original manufacturer reserves the right to make improvements to the products described in this manual at any time without notice.

No part of this manual may be reproduced, copied, translated, or transmitted in any form or by any means without the prior written permission of the original manufacturer. Information provided in this manual is intended to be accurate and reliable. However, the original manufacturer assumes no responsibility for its use, or for any infringements upon the rights of third parties that may result from its use.

The material in this document is for product information only and is subject to change without notice. While reasonable efforts have been made in the preparation of this document to assure its accuracy, GIGAIPC assumes no liabilities resulting from errors or omissions in this document, or from the use of the information contained herein.

GIGAIPC reserves the right to make changes in the product design without notice to its users.

Acknowledgement

All other products' name or trademarks are properties of their respective owners.

- AMD is trademark of Advanced Micro Devices.
- Microsoft Windows is a registered trademark of Microsoft Corp.
- Intel, Pentium, Celeron, and Xeon are registered trademarks of Intel Corporation
- Core, Atom are trademarks of Intel Corporation
- ITE is a trademark of Integrated Technology Express, Inc.
- IBM, PC/AT, PS/2, and VGA are trademarks of International Business Machines Corporation.

All other product names or trademarks are properties of their respective owners.

Packing List

Before setting up your product, please make sure the following items have been shipped:

Item	Quantity
System kit	1
19V / 65W adapter	1
Power cord (May vary based on local distribution)	1
VESA Bracket	1
VESA screw, M4-10L x 4pcs, M3-3L x 2pcs	1
HDD screw, M3 x 8L	4
FFC SATA Cable	1
Dehydrate (10G)	1
Thermal pad for HDD	2

If any of these items are missing or damaged, please contact your distributor or sales representative immediately.

About this Document

This User's Manual contains all the essential information, such as detailed descriptions and explanations on the product's hardware and software features (if any), its specifications, dimensions, jumper/connector settings/definitions, and driver installation instructions (if any), to facilitate users in setting up their product.

Users may refer to the GIGAIPC.com for the latest version of this document.

Safety Precautions

Please read the following safety instructions carefully. It is advised that you keep this manual for future references

1. All cautions and warnings on the device should be noted.
2. Make sure the power source matches the power rating of the device.
3. Position the power cord so that people cannot step on it. Do not place anything over the power cord.
4. Always completely disconnect the power before working on the system's hardware.
5. No connections should be made when the system is powered as a sudden rush of power may damage sensitive electronic components.
6. If the device is not to be used for a long time, disconnect it from the power supply to avoid damage by transient over-voltage.
7. Always disconnect this device from any AC supply before cleaning.
8. While cleaning, use a damp cloth instead of liquid or spray detergents.
9. Make sure the device is installed near a power outlet and is easily accessible.
10. Keep this device away from humidity.
11. Place the device on a solid surface during installation to prevent falls
12. Do not cover the openings on the device to ensure optimal heat dissipation.

13. Watch out for high temperatures when the system is running.
14. Do not touch the heat sink or heat spreader when the system is running
15. Never pour any liquid into the openings. This could cause fire or electric shock.
16. As most electronic components are sensitive to static electrical charge, be sure to ground yourself to prevent static charge when installing the internal components. Use a grounding wrist strap and contain all electronic components in any static-shielded containers.
17. If any of the following situations arises, please the contact our service personnel:
 - i. Damaged power cord or plug
 - ii. Liquid intrusion to the device
 - iii. Exposure to moisture
 - iv. Device is not working as expected or in a manner as described in this manual
 - v. The device is dropped or damaged
 - vi. Any obvious signs of damage displayed on the device
18. **DO NOT LEAVE THIS DEVICE IN AN UNCONTROLLED ENVIRONMENT WITH TEMPERATURES BEYOND THE DEVICE'S PERMITTED STORAGE TEMPERATURES (SEE CHAPTER 1) TO PREVENT DAMAGE.**

FCC Statement

Warning!



This device complies with Part 15 FCC Rules. Operation is subject to the following two conditions: (1) this device may not cause harmful interference, and (2) this device must accept any interference received including interference that may cause undesired operation.

Caution:

There is a danger of explosion if the battery is incorrectly replaced. Replace only with the same or equivalent type recommended by the manufacturer. Dispose of used batteries according to the manufacturer's instructions and your local government's recycling or disposal directives.

Attention:

Il y a un risque d'explosion si la batterie est remplacée de façon incorrecte. Ne la remplacer qu'avec le même modèle ou équivalent recommandé par le constructeur. Recycler les batteries usées en accord avec les instructions du fabricant et les directives gouvernementales de recyclage.






Table Contents

QBiX Industrial Embedded System	1
Quick Start Guide	1
Copyright Notice	2
Acknowledgement	3
Packing List.....	4
About this Document	5
Safety Precautions	6
FCC Statement.....	8
Chapter 1 - Product Specifications	11
1.1 Specifications	13
Chapter 2 – QBiX Industrial Embedded System Kit	15
2.1 Dimension	16
2.2 Getting Familiar with Your Unit.....	17
2.3 A) Wireless Module : How to safely install the Module (Wireless Module inclusion may vary based on local distribution)	19
2.4 B) Memory Installation: DDR4 SO-DIMM	20
2.5 Antenna Installation (Antenna inclusion may vary based on local distribution)	21
2.6 VESA Bracket	22
2.7 Support	23
2.8 Safety and Regulatory Information.....	24


Chapter 3 – Hardware Information	25
3.1 Jumpers and Connectors	26
3.2.1 EDP (Embedded Display Port Connector).....	27
3.2.2 CPU_FAN	28
3.2.3 DC_IN.....	29
3.2.5 F_USB2_1, F_USB2_2 (USB 2.0 Header).....	30
3.2.6 F_PANEL (Front Panel Header).....	31
3.2.7 SATA_PWR_0 (SATA Power Connector).....	32

Chapter 1

Chapter 1 - Product Specifications



QBiX-GLK-5005H-A1 System with Rubbed Stand
Weight : 764g (bare-bone)



1.1 Specifications


System	QBiX-GLKA5005H-A1 (GB-CGAA-SI)
Dimension	System Size : 118W x 109.4D x 54.4H (mm)
CPU	Intel® Pentium® Silver J5005 Processor 14nm, 4 cores, 4 threads, up to 2.8 GHz TDP 10W 4MB Cache
Chipset	SoC
Memory	1 x DDR4 SO-DIMM socket, Max. Capacity 8 GB Support Single Channel DDR4 2400 MHz memory modules
Ethernet	1 x GbE LAN port (Realtek® RTL8111HS)
Graphic support	Integrated Graphics Processor - Intel® UHD Graphics 605: 1 x HDMI 1.4b port, supporting a maximum resolution of 4096x2160 @30Hz 1 x VGA port, supporting a maximum resolution of 2560x1600 @60Hz (with compatible displays) (2 independent display outputs)
Audio	Realtek® Audio Codec
Storage	1 x 2.5" HDD/SSD (SATA 6Gb/s)
Expansion Slots	1 x 2230 M.2 E-Key (WiFi/BT)
Front I/O	2 x USB 3.2 Gen 1 1 x COM Port (RS-232) 1 x Headphone Jack 1 x Microphone Jack 1 x Power button with LED
Rear I/O	1 x RJ45 LAN Port 2 x USB 3.2 Gen 1 1 x HDMI 1 x VGA 2 x External Antenna (optional)
Side I/O	1 x DC-Jack
Power	+12~19VDC Full Range (Adapter 19V/65W)

System	QBiX-GLKA5005H-A1 (GB-CGAA-SI)
Operation temperature	Operating temperature: 0°C to 50°C Operating humidity: 0-90% (non-condensing) Non-operating temperature: -40°C to 85°C Non-operating humidity: 0%-95% (non-condensing) Use wide temperature range memory and storage
Vibration During Operation	Operation: IEC 60068-2-64, 5 Grms, random, 5 ~ 500 Hz, 1 hr / Per Axis, With SSD Non-operation: IEC 60068-2-6, 2 G, Sine, 10 ~ 500 Hz, 1 Oct/ min, 1 hr / Per Axis
Shock During Operation	Operation: IEC 60068-2-27, 50 G, half sine, 11 ms duration, with SSD
Packaging Content	Box Packing Capacity: 6pcs Carton size: 416x409x296(mm) Content: POWER CORD 3Cx18AWG SVT US x 1 (P/N: 25CP0-007001-Q0R) PSU ADP 19V 65W 100-240VAC x 1 (P/N: 25EP2-10065M-F3S) VESA_RS_BKT_KP x 1 (P/N: 25HB1-TPL021-S8R) VESA-SCREW-ASM x 1 (P/N: 25KSD-000001-S4R) SCREW I HEAD FOR 25HDD M3x8L x 4 (P/N: 25KSG-130081-K1R) THERMAL PAD HDD x 2 (P/N: 25ST3-200047-T5R) CABLE FFC SATA x 1 (P/N: 25CFE-100004-J3R)
Order Information	6BCGAAMR-SI (Box packing)
Optional kit:	TPM 2.0 module P/N: 9CTM000NR-00 TPM Cable P/N: 25CRZ-100600-S9R

Chapter 2

Chapter 2 – QBiX Industrial Embedded System Kit


2.1 Dimension




QBIX-GLK-5005H-A1 System with Rubbed Stand
Weight : 764g (bare-bone)

2.2 Getting Familiar with Your Unit


[Front Side]




[Left Side]



[Rear Side]




[Right Side]




[Install]

- * Before opening the case, make sure to unplug the power cord.
- * 打開機殼前，請確實移除電源。
- * Before Connecting the power, make sure to fasten the case securely.
- * 接上電源前，請確實將機殼完整鎖附。



[Bottom PCB Side]

Information	
A	M.2 2230 WiFi module connector
B	DDR4 2400 MHz SO-DIMM Slot
C	FFC SATA connector




2.3 A) Wireless Module : How to safely install the Module (Wireless Module inclusion may vary based on local distribution)

1

Carefully insert the wireless module into the M.2 slot


小心地將無線模組安裝於M.2插槽中。



2

Lock the screw in the middle.


鎖入固定於無線模組中央頂端的螺絲。



3

Install the antenna on the left side of the connection wireless module down.

向下安裝連結於無線模組左側頂端天線。




2.4 B) Memory Installation: DDR4 SO-DIMM

①

Carefully insert SO-DIMM memory modules.


小心地由下至上將 SO-DIMM 記憶體安裝於記憶體插槽。



②

Push down until the modules click into place.


當記憶體固定於插槽後，再輕輕下壓至定點。



③

Carefully insert SO-DIMM memory modules.


安裝下層記憶體後，重覆前述動作安裝上層記憶體。



④

Push down until the modules click into place.


當記憶體固定於插槽後，再輕輕下壓至定點。



2.5 Antenna Installation (Antenna inclusion may vary based on local distribution)


①

Carefully insert the antennas into the connectors.
小心地將天線插入天線插孔中。




②

Turn the antennas clockwise until they are completely secure on the connectors.
握住天線接頭底端，按順時針方向將天線旋入插孔中牢牢固定。



③

Flip up the antenna heads so that they are perpendicular to the machine.
栓緊後請將天線拉起朝上呈垂直狀。




2.6 VESA Bracket

1

Attach the screws provided on the underside of the QBiX system.


安裝隨附的VESA支撐架螺絲於QBiX底部。



2

Attach the VESA mounting plate to the rear of a compatible display using the screws provided.


安裝隨附的 VESA 支撐架於支援 VESA 支撐架的電腦螢幕或電視機後背。



3

The QBiX can now be mounted by sliding the device into place.

將已安裝VESA支撐架螺絲的QBiX插入VESA支撐架的滑軌孔，向下壓至定位點後即可固定。



2.7 Support

- For a list of tested memory, M.2, 2.5" SSD, wireless adapters and OS supported, go to: <http://www.gigaipc.com>
- To download the latest drivers and BIOS updates, go to: <http://www.gigaipc.com>
- For product support, go to: <http://www.gigaipc.com>

2.8 Safety and Regulatory Information

Risk of explosion if the battery is replaced with an incorrect type. Batteries should be recycled where possible.

Disposal of used Batteries must be in accordance with local environmental regulations.

Failure to use the included Power Adapter may violate regulatory compliance and may expose the user to safety hazards.

HDMI™
HIGH DEFINITION MULTIMEDIA INTERFACE




At the end of its serviceable life, this product should not be treated as household or general waste. It should be handed over to the applicable collection point for the recycling of electrical and electronic equipment, or returned to the supplier for disposal.

Chapter 3

Chapter 3 – Hardware Information



3.1 Jumpers and Connectors



No	Code	Description
1	EDP	Embedded Display Port Connector
2	CPU_FAN	FAN
3	DC_IN	—
5	F_USB2_1 F_USB2_2	USB 2.0 Header
6	F_PANEL	Front Panel Header
7	SATA_PWR_0	SATA Power Connector

3.2.1 EDP (Embedded Display Port Connector)



1



Pin No.	Definition	Pin No.	Definition
1	NC	21	+LCD_VCC (5V)
2	GND	22	NC
3	EDP_LANN3	23	GND
4	EDP_LANP3	24	GND
5	GND	25	GND
6	EDP_LANN2	26	GND
7	EDP_LANP2	27	EDP_HPDP_3V3
8	GND	28	GND
9	EDP_LANN1	29	GND
10	EDP_LANP1	30	GND
11	GND	31	GND
12	EDP_LANN0	32	EDP_BKLTEN_3V3
13	EDP_LANP0	33	EDP_BKLTCTL_3V3
14	GND	34	NC
15	EDP_AUX_C_DP	35	NC
16	EDP_AUX_C_DN	36	+BL_PWR (DCIN)
17	GND	37	+BL_PWR (DCIN)
18	+LCD_VCC (5V)	38	+BL_PWR (DCIN)
19	+LCD_VCC (5V)	39	+BL_PWR (DCIN)
20	+LCD_VCC (5V)	40	NC

3.2.2 CPU_FAN



2



Pin No.	Definition
1	GND
2	5V
3	Detect
4	Speed Control

3.2.3 DC_IN



3



Pin No.	Definition
1	DCVIN (PIN)
2	GND (RING)

3.2.5 F_USB2_1, F_USB2_2 (USB 2.0 Header)


5




Pin No.	Definition
1	FUSEVCC
2	USBN5_C
3	USBP5_C
4	GND

3.2.6 F_PANEL (Front Panel Header)

6





F_PANEL (Front Panel Header)



Pin No.	Definition
1	SATA_LED_P
2	MPD_+
3	GND (SATA_LEN_N)
4	MPD-
5	—
6	-PANSHW (Power BTN)
7	PMU_RSTBTN_N (Reset BTN)
8	—
9	+V3.3A
10	—

3.2.7 SATA_PWR_0 (SATA Power Connector)

7



Pin No.	Definition
1	+V5S
2	+V5S
3	+V3.3S
4	GND
5	GND